

PAPER • OPEN ACCESS

## Augmented reality for SCADA

To cite this article: Sergey V Byvaltsev 2020 *IOP Conf. Ser.: Mater. Sci. Eng.* **862** 052022

View the [article online](#) for updates and enhancements.



The banner features a background image of Earth from space. On the left, there are three circular logos: the top one says 'ECS', the middle one says 'The Electrochemical Society', and the bottom one says 'THE KOREAN ELECTROCHEMICAL SOCIETY'. In the center, a white text box contains the text: 'The best technical content in electrochemistry and solid state science and technology!'. Below this, a blue banner reads 'Available until November 9, 2020.' On the right, the 'PRIME' logo is displayed in large blue letters, with 'PACIFIC RIM MEETING ON ELECTROCHEMICAL AND SOLID STATE SCIENCE' underneath. Below that, the year '2020' is shown in large white letters on a blue background. At the bottom right, a dark blue box contains the text 'REGISTER TO ACCESS CONTENT FOR FREE!' with a right-pointing arrow.

**ECS**  
**The Electrochemical Society**  
**THE KOREAN ELECTROCHEMICAL SOCIETY**

**The best technical content in  
electrochemistry and solid state  
science and technology!**

**Available until November 9, 2020.**

**PRIME<sup>TM</sup>**  
**PACIFIC RIM MEETING**  
**ON ELECTROCHEMICAL**  
**AND SOLID STATE SCIENCE**

**2020**

**REGISTER TO ACCESS  
CONTENT FOR FREE! ▶**

# Augmented reality for SCADA

**Sergey V Byvaltsev**

Ural Federal University named after the First President of Russia B. N. Yeltsin, 19,  
Mira St., Ekaterinburg, 620002, Russian Federation  
Institute of Engineering Science, Ural Branch of the Russian Academy of Sciences,  
34, Komsomolskaya St., Ekaterinburg, 620049, Russian Federation

E-mail: s\_ikar@mail.ru

**Abstract.** Questions of construction of the Augmented Reality for application in SCADA-systems are considered. It is marked, that last years researchers from Russia actively started studying this branch. The author considers the augmented reality in a section of a reality-virtuality continuum taking into account restrictions of memory of the operator and social aspect of application augmented reality. Recommendations on environmental analysis and reading of data from display devices are given. The greatest efficiency of application augmented reality is seen in joint activity and carrying out of works which demand coordinated work. The necessity of the further researches for developing of network architecture, safety, confidentiality and protection against extraneous intervention is noted. Advantage of augmented reality is reuse of software, databases and knowledge. At the replacement of maintenance staff and users of SCADA-system there is no need to teach them all the knowledge and skills at once. They will receive them directly in the process of application.

## 1. Introduction

The augmented reality is penetrating more and more into different fields of activity, including education and industry. Since 1993, the annual IEEE Virtual Reality International Symposium has been held, and since 2002, the annual IEEE International Symposium on Mixed and Augmented Reality has been held, which discusses various issues in the construction of virtual, mixed and augmented reality. Since 2007, the IEEE International Conference on Industrial Engineering and Engineering Management and many other conferences have been held. At the same time, in 2010-2012 Russia was on the 18th place in the rating of countries by the number of patent applications on "virtual and augmented reality technologies". By 2015-2017, Russia has moved up by one place in this ranking. The leaders of the rating are organizations from the USA, China, Japan and the Republic of Korea. In a similar ranking of countries by the number of publications indexed by Scopus, Russia moved up from 42nd place in 2010 to 18th place by 2018. Realizing the importance of advanced technologies for the society development, the Ministry of Digital Development, Communications and Mass Media of the Russian Federation has created the Roadmap for "Trans-through" digital technology development "Technology of virtual and augmented reality" [1].

## 2. Augmented reality in a continuum of reality and virtuality

The mixing of physical and digital worlds defines the combination of real and virtual environments and becomes a part of the Reality-Virtuality Continuum (RVC) [2], [3]. The RVC describes the interactions between reality and virtuality. In RVC, augmented reality (AR) is the depiction of virtual objects in the context of the real world. Modern AR solutions on portable devices use an image from a real device and



Content from this work may be used under the terms of the [Creative Commons Attribution 3.0 licence](#). Any further distribution of this work must maintain attribution to the author(s) and the title of the work, journal citation and DOI.

combine it with virtual content. Similar solutions exist for transparent (head-mounted) displays (for example, Magic Leap One Personal Bundle, Microsoft HoloLens 2, Epson MOVERIO, EverySight Raptor, Google Glass Enterprise Edition 2, Kopin SOLOS, Meta 2, ODG R-7, Toshiba dynaEdge AR100, Vuzix Blade Smart Glasses, ThirdEye Gen X2, Vuzix M4000). Modern AR applications also include tactile feedback and spatial sound [4], [5].

### **3. Considerations of operators' memory limits**

The use of AR to increase the capabilities of SCADA-systems is an undoubted advantage, but it is necessary to develop special intelligent SCADA-systems with AR support and operators training this technology. And it is necessary to dose the amount of information submitted through AR, because operators may become dependent on system prompts and reduce the willingness to solve problems independently, and sometimes the inability to perform the same actions without using AR [6]. For this purpose it is suggested to reduce the flow of new information during operators' training because it is possible that the operator will not notice really important information. In addition you should remove insignificant or irrelevant information (representations) for the running process.

Cognitive load theory builds on the widely-accepted assumption that humans have limited working memory capacity and further asserts that each instructional condition imposes on working memory three types of cognitive load: 1) intrinsic cognitive load; 2) extraneous cognitive load; and 3) germane cognitive load [7], [8]. Whereas intrinsic cognitive load is determined by the complexity (i.e., "element interactivity") of the learning task itself and germane load is associated with conscious, constructive processes used to construct mental representations, extraneous load does not contribute to learning. Furthermore, if working memory capacity is fully engaged in processes related to intrinsic and extraneous load, learners will have no remaining cognitive resources to allocate to germane processes, and little learning can occur. According to the Four-component Instructional Design (4C/ID) model [9], learning tasks should be ordered such that earlier tasks include lower element interactivity (i.e., low intrinsic cognitive load) and as learning tasks become more complex, instructional scaffolds should be provided to reduce extraneous load during transitions to more difficult material.

According the schematic theoretical model of concreteness fading the process of training operators is effectively carried out in three stages [10]. At the first stage, training is carried out on concrete examples, when it is easier for an operator to interpret ambiguous abstract representations in terms of well understood concrete objects, and also the advantages of embodied cognition are used, which gives experience of working with physical and perceptual processes, which are limited and therefore give correct conclusions [11], [12]. The operator remembers a set of attributes (images, symbols, gestures, etc.) which will be used in the AR system metaphor when abstract symbols are related to real objects. After understanding the abstract concept in solving new problems, the operator will rely on this set of attributes [13]. At other two stages there is a move from real physical representation to graphic schemes and models, and then to usual abstract symbols [13].

This moment requires further research, since according to [14] the transition from abstract to concrete can sometimes improve learning.

Thus, in training, the intelligent AR system will adapt itself to the operator's gained experience in servicing systems and facilities. There will be a transition from a specific instruction of the required sequence of each action [15] to monitoring the execution of these actions and fixing the fact of execution of the embedded instructions.

### **4. Social aspect of AR application in SCADA**

Most often purely technical aspects of AR environment design are investigated. Only recently it began to notice that it is necessary to consider social aspect of application AR. Users develop a sense of interconnection and psychological belonging to virtual artifacts in AR environment more, than in the usual virtual environment. A common environment in the interaction of several participants may disturb the sense of identity of users, as well as potentially threaten the sense of personal space and the sense of physical objects [16], [17]. The assessment of perception when using glasses and the hand-held device (smartphone) is studied in [18].

Sensors placed on the body can be used to transmit feedback to the AR system and interact with the operator. However, some actions are easier to perform in the street than in a public place, because some gestures are simply not permitted there [19]. To transmit control commands to the SCADA system, it is necessary to take into account that some gestures and movements of the operator may be related not to the control process, but to the performance of any other work, maintenance of the installation or random movements. It is necessary to further develop a special protocol to prevent the execution of wrong commands.

Also with the use of AR, there can be discomfort and a negative reaction to interpersonal disturbances [20].

It can be assumed that the use of AR in SCADA-systems will be more effective, if in addition to the execution of commands and sensor readings AR will visualize these processes using the familiar to the operator external environment, especially in remote management. In recent years, four different agents: voice-only, non-human, full-size embodied, and a miniature embodied agent [21] are used for this purpose. Besides, for an operator it is necessary to increase the level of user's perceived trust in the intellectual system. For example, for users of Internet of Things (IoT) devices using AR, the level of trust was much higher than only with Voice-activated Intelligent Virtual Assistants (IVAs) such as Amazon Alexa [22].

In the process of training for working with AR it is necessary to move from the virtual environment to the real world, when the operator is given only the necessary dosing information and is controlled and checked the correctness of his actions. It is suggested to use multi-level scenarios of data display [23] for different types of staff and qualifications, for example, displaying only the current temperature, its graph in the near future, its extrapolation to the future, or only a message in case of deviation from expected, etc.

Analogously, in order to present data, it is necessary to move from a real physical representation to an abstract one.

Nowadays AR is widely used directly for training process [24], though in our opinion it is more effective to use AR for large and complex systems [25], in which it is necessary to provide reliability and stability. The purpose of AR in SCADA-systems is abstract presentation of data to the operator in real time, overlaid on the natural environment [26] even on the go [27].

## **5. Analysis of the environment**

It is possible to use the computer vision library OpenCV [28] for environmental analysis. To bind to the system it is suggested to use a markerless framework, which does not imply the use of fiducial markers [29] or even natural markers in the environment [30], [31]. At the same time, there is a problem of providing AR plasticity [32], [33]. Properties of the presented additions are modified according to the values of the use context, the platform applied and the properties of the environment [34], for example, scene illumination [35], user position, estimated by his distance from the target and the ambient noise [36]. Most often the image of the equipment itself is processed through a calibrated camera by ARToolKit [37] or SLAM framework [38], which can be replaced by a more advanced GLEAM [39]. It should be noted that it is necessary to eliminate the perceptual problem of perception of incorrect depth interpretation of graphical objects overlaid on the real world [40], [41]. This is especially shown in stereoscopic systems, head-mounted displays, are evolving towards endless screens and natural FOVs, in which it is necessary to become more accurate in the challenging X-ray visualization and the best support for occluded interaction. Note the three most influential factors: point-of-view, view stability and view displacement [42]. For a hand-held device, this problem is less relevant [43].

While getting information about the control object it is possible to use Internet of Things (IoT) technologies [44], in particular, to use a communicating-actuating network wherein sensors and actuators blend seamlessly with the environment around us, and the information is shared across platforms in order to develop a common operating picture (COP).

Optical Character Recognition (OCR) can be used to read data from sensors that do not have a digital output and communication interface, and then converted to a digital form [45]. And the analysis is possible for both digital and pointer devices with determination of the measurement scale [46].

## 6. Results and discussion

The greatest effectiveness of AR application will be achieved through collaborative activities and work that requires coordinated work. In this case, for multiuser AR the social aspect considered earlier becomes especially actual, and also network architecture [47], [48], safety, confidentiality and protection against extraneous intervention [49].

The advantage of AR is the reuse of software, database and knowledge. When there is a replacement of service staff and system users, there is no need to teach them all the knowledge and skills. They will receive them directly during application. The qualification requirements for the users are considerably reduced, but the requirements for the maintenance system (software, databases and knowledge, rules and models) are increased. Also there are fewer human errors and an opportunity to control its actions in real time. EcoStruxure Augmented Operator Advisor enables technicians to locate the right equipment and guides them step-by-step to complete the procedures.

Certain problems may present the possibility of AR operation without network access [50], in offline mode, but AR designers for industry offer the use of communication sessions and special tickets.

Despite difficulties with implementation AR in the industry, the advanced producers of automation means already offer ready decisions.

AR is necessary to apply first of all for serial products or for objects where the big replacement of staff, and also for difficult systems in which it is necessary to exclude human errors [51], [52].

## Acknowledgements

The author expresses his gratitude to the staff of the Department of Information Technologies and Design Automation of Ural Federal University and the staff of the Laboratory of System Modelling of the Institute of Engineering Science, Ural Branch of the Russian Academy of Sciences without valuable advice and critical comments which it would be impossible to publish this study.

## References

- [1] *The Roadmap for the development "Technology of virtual and augmented reality"* Accessed at: <https://digital.gov.ru/ru/documents/6654/> (accessed 10.03.2020)
- [2] Milgram P and Kishino F 1994 *IEICE Trans. Inf & Syst.* **E77(12)** 1322-9
- [3] Milgram P, Takemura H, Utsumi A and Kishino F 1994 *SPIE, Telemanipulator and Telepresence Technologies* **2351** 282-92
- [4] Goose S, Sudarsky S, Zhang X, and Navab N 2003 *IEEE Pervasive Computing* **2(1)** 65-70
- [5] Radu I and Schneider B 2019 *Proc. of the 2019 CHI Conf. on Human Factors in Computing Systems (CHI '19)* (New York: ACM) pp 544:1-12
- [6] Woo W 2018 *Proc. of the 3rd Int. Workshop on Multimedia Alternate Realities (AltMM'18)* (New York: ACM) p 1
- [7] Sweller J, Merrienboer J J G and Paas F W C 1998 *Educational Psychology Review* **10** 251-96
- [8] Baddeley A D 1983 *Phil. Trans. R. Soc. Lond. B* **302(1110)** 311-24
- [9] Merrienboer J J G and Sluijsmans D M A 2009 *Educational Psychology Review* **21(1)** 55-66
- [10] Fyfe E R, Neil N M, Son J Y and Goldstone R L 2014 *Educational Psych. Review* **26(1)** 9-25
- [11] Barsalou L W 2003 *Language & Cognitive Processes* **18** 513-62
- [12] Lakoff G and Nunez R E 2000 *Where mathematics comes from: how the embodied mind brings mathematics into being* (New York: Basic Books) p 493
- [13] Bruner J S 1966 *Toward a theory of instruction* (Cambridge: Belknap) p 192
- [14] Johnson A M, Reisslein J and Reisslein M 2014 *Computers & Education* **72** 249-61
- [15] Raghavan V, Molineros J and Sharma R 1999 *IEEE Transactions on Robotics and Automation* **15(3)** 435-49
- [16] Poretski L, Lanir J, Arazy O and Oded N 2019 *Proc. of the 1st Workshop on Challenges Using Head-Mounted Displays in Shared and Social Spaces CHI'19 Extended Abstracts* (Glasgow, Scotland UK) p 6
- [17] Poretski L, Lanir J and Arazy O 2018 *Proc. of the ACM on Human-Computer Interaction (PACMHCI)* **2(CSCW)** pp 142:1-24
- [18] Koelle M, Kranz M and Möller A 2015 *Proc. of the 17th Int. Conf. on Human-Computer*

- Interaction with Mobile Devices and Services MobileHCI '15* 362-72
- [19] Williamson J R, Crossan A and Brewster S 2011 *Proc. of the 13th Int. Conf. on Multimodal Interfaces ICMI '11* 361-8
  - [20] Wilcox L M, Allison R S, Elfassy S and Grelik C 2006 *ACM Transactions on Applied Perception* **3(4)** 412-28
  - [21] Wang I, Smith J and Ruiz J 2019 *Proc. of the Conf. on Human Factors in Computing Systems (CHI 2019)* (New York: ACM) pp 281:1-10
  - [22] Haesler S, Kim K, Bruder G and Welch G 2018 *IEEE Int. Symp. on Mixed and Augmented Reality Adjunct (ISMAR-Adjunct)* pp 204-5
  - [23] Reuter R, Knietzsch M, Hauser F and Mottok J 2019 *Proc. of the 2019 ACM Conf. on Innovation and Technology in Comp. Sc. Education (ITiCSE '19)* (New York: ACM) p 320
  - [24] Manoela S, Teichrieb V and Smith P 2019 *Anais dos Workshops do VIII Congresso Brasileiro de Informática na Educação (WCBIE 2019)* pp 1452-6
  - [25] Fite-Georgel P 2011 *10th IEEE Int. Symp. on Mixed and Augmented Reality (ISMAR)* (Basel Switzerland) pp 201-10
  - [26] Masood T and Egger J 2019 *Robotics and Computer-Integrated Manufacturing* **58** 181-95
  - [27] Lages W S and Bowman D A 2019 *Proc. of the 24th Int. Conf. on Intelligent User Interfaces (IUI '19)* (New York: ACM) pp 356-66
  - [28] Pulli K, Baksheev A, Korniyakov K and Eruhimov V 2012 *Communications of the ACM* **55(6)** 61-9
  - [29] Fiala M 2005 *Proc. IEEE Computer Society Conf. on Computer Vision and Pattern Recognition (CVPR)* **2** 590-6
  - [30] Gomes D L, de Paiva A C, Silva A C, Braz G, de Almeida J D S, de Araújo A S and Gattas M. 2018 *Computers in Industry* **97** 67-75
  - [31] Georgel P, Schroeder P, Benhimane S, Hinterstoisser S, Appel M and Navab N 2007 *6th IEEE and ACM Int. Symp. on Mixed and Augmented Reality* (Nara, Japan: IEEE) pp 111-5
  - [32] Calvary G, Coutaz J, Daassi O, Ganneau V, Balme L and Demeure A 2006 *10 ème conference ERGO-IA, L'humain comme facteur de performance des systèmes complexes*
  - [33] Calvary G and Coutaz J 2007 *Revue d'Interaction Homme-Machine* **1**
  - [34] Thevenin D 2001 *Adaptation en Interaction Homme- Machine : le cas de la Plasticité Thèse de l'Université Joseph Fourier* (Grenoble I, France) p 235
  - [35] Grosch T, Eble T and Mueller S 2007 *Proc. of the 2007 ACM symp. on Virtual reality software and technology* (New York: ACM) pp 125-32
  - [36] Ghouaiel N, Cieutat J-M and Jessel J-P 2014 *Laval Virtual VRIC'14* (Laval, France)
  - [37] Kato H and Billinghurst M 2004 *3rd IEEE and ACM Int. Symp. on Mixed and Augmented Reality (ISMAR 2004)* (Arlington VA USA: IEEE) p 305
  - [38] Tamaazousti M, Naudet-Collette S, Gay-Bellile V, Bourgeois S, Besbes B and Dhome M 2016 *Multimedia Tools and Applications* **75** 9511-47
  - [39] Prakash S, Bahremand A, Nguyen L D and LiKamWa R 2019 *Proc. of the 17th Annual Int. Conf. on Mobile Systems, Applications, and Services (MobiSys'19)* (New York: ACM) pp 142-54
  - [40] Kruijff E, Swan J, and Feiner S 2010 *Proc. of the 9th IEEE Int. Symp. on Mixed and Augmented Reality (ISMAR)* (Los Alamitos, CA: IEEE) pp 3-12
  - [41] Kytö M, Mäkinen A, Häkkinen J and Oittinen P 2013 *ACM Transactions on Applied Perception* **10(1)** 6:1-21
  - [42] Liliya K, Pohl H, Boring S and Hornbæk K 2019 *Proc. of the 2019 CHI Conf. on Human Factors in Computing Systems (CHI 2019)* (New York: ACM) pp 446:1-12
  - [43] Sailer C, Rudi D, Kurzhals K and Raubal M 2019 *18th World Conf. on Mobile and Contextual Learning: Future Learning Through Experiences and Spaces (mLearn 2019)* (Delft, Netherlands) pp 69-76
  - [44] Gubbi J, Buyya R, Marusic S and Palaniswami M 2013 *Future Generation Computer Systems* **29** 1645-60
  - [45] Lu H, Guo B, Liu J and Yan X 2017 *10th Int. Congress on Image and Signal Processing, BioMedical Engineering and Informatics (CISP/BMEI)* p. 1-5

- [46] Bojaca E, Anzola J, Jiménez A and García-Díaz V 2018 *Computers and Electrical Engineering* **71** 533-45
- [47] Ruth K, Kohno T and Roesner F 2019 *Proc. of 28th USENIX Security Symp.* (Santa Clara, CA, USA: USENIX Association) pp 141-58
- [48] Lebeck K, Kohno T and Roesner F 2019 *Proc. of 20th Int. Workshop on Mobile Computing Systems and Applications (HotMobile '19)* (New York: CM) pp 81-6
- [49] Soh L, Burke J and Zhang L 2018 *Proc. of VR/AR Network '18* (Budapest, Hungary) pp 1-6
- [50] Han Y, Lee C, Kim S and Ko S 2019 *Proc. of the 17th Annual Int. Conf. on Mobile Systems, Applications, and Services (MobiSys '19)* (New York: ACM) pp 522-3
- [51] Gimeno J, Casas S, Portales C and Fernandez M 2019 *DYNA* **94(2)** 155-60
- [52] Hofmann C, Staehr T, Cohen S, Stricker N, Haefner B and Lanza G 2019 *Procedia Manufacturing* **31** 148-54